

OMNITRONIC MCD-2004 MK2 4-Channel Installation Amplifier

4-channel PA amplifier with SMPS, 4 ohms: 4 x 500 W, 8 ohms: 4 x 250 W

Art. No.: 10452414

GTIN: 4026397700206



List price: 593.81 €

incl. 19% VAT.

Features:

- PA amplifier with integrated limiter for multi-zone applications
- Signal inputs via balanced XLR mounting jacks and terminal blocks
- Speaker connection via terminal blocks
- Tamper-proof level adjustment on the rear panel
- 3-fold output meter with clip LED per channel
- Speaker switch-on delay
- Rugged steel chassis with aluminum front panel
- Complete protection set
- Air flow from front to rear
- The device is cooled by cooling fan
- (19") 48.3 cm rack installation 2 U

Package contents

- 1 x amplifier, 1 x power cord, 4 x screw terminal, 4 x feet, 4 x screw, 1 x user manual

Logistic

EAN / GTIN: 4026397700206

Weight: 8,50 kg

Length: 0.53 m

Width: 0.45 m

Height: 0.15 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	350 W 1/8 power
Output power:	4 x 250 W RMS (8 ohms) 4 x 500 W RMS (4 ohms)
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Frequency range:	22 - 25000 Hz

S/N ratio:	>120 dB
THD:	<0,003 % at 1 kHz
Cooling:	1 x cooling fan , Air flow from front to rear
Impedance:	Input 22 kOhm , bal. Input 12 kOhm , unbal.
Gain:	26 dB
Circuitry:	Class D
Slew rate:	>10 V/ μ s
Damping factor:	>500
Control elements:	Power switch, level control per channel
Controls:	Overheat; short-circuit; softstart; overload; DC voltage; power on/off transient
Status LED:	Power, level meter, clip, protect
Connections:	Input: line via 4 x 3-pin XLR Input: line via 4 x screw terminal Output: speaker via 4 x screw terminal
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm Depth: 38,8 cm Height: 8,9 cm
Weight:	7,45 kg