

OMNITRONIC DMF-2 DJ multi filter

High-quality DJ sound effect device





The article is no longer in our assortment.

Features:

- Hi-Pass and Lo-Pass filters

- Variable Cut-Off & resonance per filter
- Filter characteristics switchable between band & notch
- Band/notch, phono, trigger and bypass switch
- Input level adjustable
- Line & phono input
- Turntable grounding terminal
- 1/3 rack unit

Technical specifications:

Power consumption:	6,00 W
Dimensions:	Width: 14,5 cm
	Depth: 13,4 cm
	Height: 3,4 cm
Weight:	0,59 kg
Power supply:	10 V AC, 600 mA
	via power unit included in the delivery
Electrical:	
Frequency range:	20-20000 Hz, ±1 dB
Dynamic range:	>109 dB, A-weighting

Logistic

EAN / GTIN: 4026397157871 Weight: 1,10 kg Length: 0.18 m Width: 0.12 m Heigth: 0.18 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

-90 dB
-90 UD
2 (stereo)
RCA
20-20000 Hz, ±1 dB
<0.01% @ 1 kHz
- 10 dBu
+ 22 dBu
45 kohms, unbalanced
2 (stereo)
RCA
- 10 dBu, front panel adjustable
+ 20 dBu
100 kohms
145 x 134 x 34 mm