OMNITRONIC CMP-1000 Dual CD/MP3 player

Dual CD player with MP3 function for DJs

Art. No.: 10602405

GTIN: 4026397270136

The article is no longer in our assortment.

Description:

"Back in the good old days, things were better!" This statement is not always true, but sometimes it is appropriate. With the handy CMP-1000, the truth can be seen by looking on the display. Following old tape decks, this dual-CD/MP3 player is equipped with an VFD display that guarantees an overwhelming good readability. And this makes perfect sense, as the display, with its ID3 tag provides the main information about the running data file - except for the music, of course. So details about the artist or the song will not get lost and can always be read easily.

Logistic

EAN / GTIN: 4026397270136
Weight: 10,50 kg
Length: 0.60 m
Width: 0.58 m
Heigth: 0.20 m

Features:

- For MP3 and audio CDs, CD-Rs, CD-RWs
- MP3 compatible with ID3 tag support up to 999 files and 255 folders per CD
- Alphanumerical VFD display for format, folder, file, ID3 tag and bitrate
- Jog/Shuttle wheel for quick track selection and framewise search (1/75 sec)
- Seamless Loop and Reloop function
- Single/Continuous mode
- Main Tempo function
- Faderstart function
- 2 x 10 seconds anti-shock
- Pitch adjustment ±4 %, ±8 %, ±16 %, ±100 % (MP3s up to 16%)
- Pitch adjustment via pitchfader is displayed (in % or BPM)
- Pitch Bend buttons
- Automatic and manual beat counter
- Cue function with 4 cue point hotkeys
- 2000 cue points can be memorized and recalled from up to 500 CDs
- Relay button for switching playback automatically to the other player after every track
- Open/Close buttons locked in play mode

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Display switchable from track remain time to total remain time to track playback time
- Digital output via RCA
- Exquisit design with anodized aluminum front panel
- Comfortable operation due to well-structured front panel design
- Rack installation

Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	23,00 W
Dimensions:	Width: 48,3 cm Depth: 31 cm Height: 8,9 cm
Type:	Dual Compact Disc/ MP3 player
Available disc:	Standard CDs (8 and 12 cm)
Quantisation:	D/A converter: 1 bit
Sampler frequency:	44.1 kHz
Frame accuracy:	1/75 sec
Pitch adjustment:	±4 %, ±8 %, ±16 %, ±100 %
Display:	ID3 tags, remaining track time, track playback time, total remain
Distortion:	0.006 %
S/N ratio:	90 dB
Frequency range:	20-20000 Hz, ±1 dB
Audio output:	unbalanced via RCA
Output level:	2 Vrms
Digital ouput:	unbalanced via RCA
Dimensions:	482 x 88.8 x 310 mm (CD player)
	482 x 132 x 75 mm (control unit)
	Rack installation
Weight:	6 kg (CD player)
	2.5 kg (control unit)

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.