

OMNITRONIC CMP-2000 Dual CD/MP3 Player

Dual CD player with MP3 function for DJs

Art. No.: 10602409

GTIN: 4026397478457



The article is no longer in our assortment.

Features:

- Audio CD, CD-R, CD-RW, MP3 CD
- 2 USB ports for storage media and portable players (FAT 32)
- Easy Source Select: route USB sources to both drives as desired
- Combined Device Access: both drives can access the same USB medium simultaneously
- Access music files more easily and quickly via smart music database management with free PC software Database Builder
- Sort USB devices lightning-fast by title, artist, album and genre
- System menu for user-defined settings
- 2 x 20 seconds anti-shock protection
- Outstanding reading time of the files (instant start within 10 ms)
- Automatic beat counter (switchable to manual operation)
- Master tempo (tonal pitch remains constant when speed is changed)
- 2 alphanumeric LCDs with ID3 tag indication
- Touch-sensitive jog dials with adjustable sensitivity and mode selector: scratch or pitch bend
- Pitch adjustment $\pm 4\%$, $\pm 8\%$, $\pm 16\%$, $\pm 100\%$ (MP3 CD $\pm 16\%$)
- Fader start
- Relay function
- Folder navigation
- Pitch Bend
- Cue/auto cue function
- Seamless loop/reloop
- Single or continuous play
- Repeat function
- Indication of elapsed time, remain time (MP3 files) or total remain time (audio CD)
- Bargraph display
- Pitch adjustment is displayed in %

Logistic

EAN / GTIN: 4026397478457

Weight: 7,90 kg

Length: 0.45 m

Width: 0.18 m

Height: 0.04 m

- Extra-large play/pause and cue buttons with color illumination
- Drives are locked in play mode
- Rack installation
- The Database Builder software is available in the manufacturer's download section
- Digital signal processor master tempo
- Sample rate: 44,1 kHz
- Pitch range: CD-DA $\pm 4\%$, $\pm 8\%$, $\pm 16\%$, $\pm 100\%$
- Pitch range: MP3 $\pm 4\%$, $\pm 8\%$, $\pm 16\%$

control panel

- (19") 48.3 cm rack installation 2 U

audio player

- (19") 48.3 cm rack installation 2 U

Package contents

- 1 x audio player, 1 x control panel

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	16,00 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Frequency range:	17 - 20000 Hz
S/N ratio:	>126 dB
THD:	<0,008 % at 1 kHz
DSP:	Digital signal processor master tempo
Audio player:	USB + CD player, (ID3 tag), Anti-shock, Seamless loop
Sample rate:	44,1 kHz
CD player drive:	Drawer-double CD drive
Display:	ID3-Tags , play time elapsed , play time remaining , total play time remaining
Connections:	Output: 2 x stereo RCA
Music format:	CD, CD-R, CD-RW, CD-DA, MP3
Frame accuracy:	1/75 s
Available storage media:	USB devices max. 32GB (FAT 32)
Pitch range:	CD-DA $\pm 4\%$, $\pm 8\%$, $\pm 16\%$, $\pm 100\%$ MP3 $\pm 4\%$, $\pm 8\%$, $\pm 16\%$
USB port:	2 x type A
Converter:	8-fach/ 1 bit
Weight:	6,80 kg
Audio player	
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm Depth: 26,5 cm Height: 8,9 cm
Control panel	
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm Depth: 9,5 cm Height: 8,9 cm