

OMNITRONIC PMM-4, 4" Studio monitors/pair

Active 2-way Nearfield-monitor

Art. No.: 11036460

GTIN: 4026397198782





The article is no longer in our assortment.

Features:

- Balanced frequency range for uncolored playback
- For studio use, home-recording or for high end playback in the living room
- Magnetic shielding for use next to computer monitors etc.
- Ferrofluid-cooled tweeter for brilliant treble
- Bass-reflex-system
- Level-control
- With mini-switches for adjusting the environmental conditions
- Line-signal-connection via RCA/jack socket
- Rugged MDF-wood housing
- Packed as a pair (2 pieces)

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	35,00 W
Frequency range:	70 - 20000 Hz
Dimensions:	Width: 24 cm
	Depth: 15,5 cm
	Height: 16 cm
Weight:	4,70 kg
Rated power:	15 W RMS

Logistic

EAN / GTIN: 4026397198782 Weight: 5,45 kg Length: 0.39 m Width: 0.30 m Heigth: 0.25 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Program power:	30 W
Components:	10 cm woofer (4"), 2 cm tweeter (0.75")
Connection:	RCA/jack socket
Sensitivity:	85 dB
Distortion factor:	0.05 %
Min. input sensitivity:	1 V
Input Impedance:	4 ohms
Dimensions (H x W x D):	240 x 155 x 160 mm