

OMNITRONIC PMM-5 Studio monitors/pair

Active 2-way nearfield monitors

Art. No.: 11036463

GTIN: 4026397198935



The article is no longer in our assortment.

Features:

- 5" nearfield monitors
- 2-way active version with separate power amplifiers for bass speaker and tweeter (bi-amping)
- Excellent sound for studio use, home recording or high-end playback in living rooms
- Ferrofluid-cooled tweeter for brilliant treble
- Balanced frequency range for uncolored playback
- Level control
- Magnetic shielding for use next to computer monitors etc.
- Switches for adjusting the environmental conditions
- Line signal connection via RCA/XLR/jack socket
- High-quality bass-reflex MDF cabinet
- Packed as a pair (2 pieces)

Technical specifications:

Power supply:	230 V AC, 50 Hz	
Power consumption:	75,00 W	
Frequency range:	60 - 20000 Hz	
Dimensions:	Width: 28 cm	
	Depth: 18,5 cm	
	Height: 21,5 cm	
Weight:	10,00 kg	
Rated power:	35 W RMS	



Logistic

EAN / GTIN: 4026397198935 Weight: 10,75 kg Length: 0.47 m Width: 0.40 m Heigth: 0.26 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Program power:	70 W
Components:	13 cm woofer (5"), 2 cm tweeter (0.75")
Connection:	RCA/XLR/jack socket
Sensitivity:	90 dB
Distortion factor:	0.05 %
Min. input sensitivity:	1 V
Input Impedance:	8 ohms
Dimensions (H x W x D):	280 x 185 x 215 mm