

OMNITRONIC PMS-10 Studio subwoofer

The completion for your studio monitors

Art. No.: 11036468

GTIN: 4026397222517











The article is no longer in our assortment.

Features:

- Suitable for PMM-4, PMM-5, PMM-8, PSM-6.5, PSM-6.5A and all other passive systems in need of bass support
- High efficiency
- Stereo input (XLR/6.3 mm jack)
- Stereo output and feed-through output (both XLR)
- Active 2-way crossover
- Level control
- Phase inversion switch
- High-pass filter, selectable via footswitch
- Standby mode

Logistic

EAN / GTIN: 4026397222517

Weight: 17,40 kg Length: 0.55 m Width: 0.53 m Heigth: 0.44 m

Technical specifications:

| Power supply: | 230 V AC, 50 Hz | |
|--------------------|--|--|
| Power consumption: | 250 W | |
| Frequency range: | 40 - 350 Hz | |
| Connections: | Input: speaker via 1 x 3-pin XLR Input: speaker via 1 x 6.3 mm plug (unbal.) | |
| Speaker: | 1 x woofer 10" | |
| Dimensions: | Width: 43 cm | |
| | Depth: 43 cm | |
| | Height: 31,5 cm | |

| Weight: 15,50 k | 15,50 kg | « g | |
|-------------------------|--------------------|------------|--|
| Amplifier power: | 150 W | | |
| Components: | 25 cm woofer (10") | | |
| Inputs: | XLR/6.3 mm jack | | |
| Outputs: | XLR | | |
| Footswitch: | 6.3 mm jack | | |
| Distortion factor: | 0.05 % | | |
| Min. input sensitivity: | 0.775 V | | |
| Input impedance: | 4 ohms | | |
| Dimensions (H x W x D): | 430 x 430 x 315 mm | | |