

OMNITRONIC PSS-12A Studio subwoofer

The completion for your studio monitors

Art. No.: 11036476

GTIN: 4026397207699











The article is no longer in our assortment.

Features:

- Can be used for PSM-6.5, PSM-6.5A and all other passive systems in need of bass support
- High efficiency
- Signal input via RCA, XLR or 6.3 mm plugs
- Signal output via XLR plugs
- Level control
- Low-pass filter, continuously adjustable
- Phase inversion switch
- Footswitch to switch subwoofer on/off
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4026397207699

Weight: 31,50 kg Length: 0.73 m Width: 0.55 m Heigth: 0.48 m

Technical specifications:

Power supply:	230 V AC, 50 Hz	
Power consumption:	250,00 W	
Output power:	Max. 150 W	
Frequency range:	50 - 150 Hz	
Dimensions:	Width: 45 cm Depth: 38 cm Height: 54 cm	
Weight:	27,00 kg	
Amplifier power:	150 W	

Components:	12" long excursion woofer
Inputs:	XLR/jack combination, RCA
Outputs:	XLR
Footswitch:	6.3 mm jack
Sensitivity:	90 dB
HP filter:	adjustable down to 60 Hz
THD:	0.05 %
Min. input sensitivity:	1 V
Input impedance:	10 kohms
Dimensions (H x W x D):	450 x 380 x 540 mm