

OMNITRONIC Subwoofer for Control Systems

Passive subwoofer with crossover, 6,5" woofer, 50 W RMS / 4 ohms

Art. No.: 11036580 GTIN: 4026397053517









The article is no longer in our assortment.

Features:

- The completion for your Control system
- Can be used for Control 1, Control 5, Control 100 and Control 200
- Stereo connection via screw connector
- Built-in crossover separates at 300 Hz
- High efficiency
- 16.5 cm woofer (6.5") in bandpass enclosure
- Bass-reflex tube with a diameter of 6 cm

Technical specifications:

Power:	Program: 150W Rated: 50W RMS
Frequency range:	50 - 130 Hz
Sensitivity:	85 dB (1W/1m)
Max. SPL:	91 dB
Connections:	Input: speaker via spring terminal
Speaker:	1 x woofer 6,5"
Color:	Black
Dimensions:	Width: 35 cm
	Depth: 42 cm
	Height: 25 cm

Logistic

EAN / GTIN: 4026397053517 Weight: 10,75 kg Length: 0.49 m Width: 0.43 m Heigth: 0.34 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Weight:	9 kg	
Components:	16.5 cm woofer (6.5")	
Connection:	stereo / 2-pole terminals	
Sensitivity:	85 dB	
Maximum SPL:	91 dB	