

## **OMNITRONIC C-60A active white 2x**

Active 2-way speaker pair with mount, 6,5" woofers and 60 W RMS

Art. No.: 11036721 GTIN: 4026397356373





## Features:

- Dedicated PA speaker system for fixed installations
- 2-way bass-reflex system for powerful bass
- 16.5 cm woofer (6.5") and 2.5 cm dome tweeter (1")
- 2-way tone control and level control
- Signal input and output via balanced XLR connectors
- White or titanium plastic housing (ABS) with metal grille
- Trapezoidal cabinet for corner installation
- Movable mounting bracket for ceiling or wall installation
- Ideal for PA applications in restaurants, bars, discos, shops, conferences, etc.

## **Technical specifications:**

Power supply:	230 V AC, 50 Hz
Power:	Program: 100W Rated: 60W RMS
Frequency range:	50 - 20000 Hz
Sensitivity:	89 dB (1W/1m)
Connections:	Input: speaker via 2 x 3-pin XLR
Speaker:	1 x woofer 6,5"
Color:	White
Dimensions:	Width: 20,5 cm



EAN / GTIN: 4026397356373 Weight: 9,70 kg Length: 0.43 m Width: 0.24 m Heigth: 0.34 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Depth: 18 cm Height: 28,5 cm
Weight:	9,10 kg
Components:	16.5 cm woofer (6.5"), 2.5 cm tweeter (1")
Input:	3-pin XLR
Output:	3-pin XLR
Sensitivity:	89 dB
Dimensions (H x W x D):	285 x 205 x 180 mm