

OMNITRONIC C-80A active black 2x

Active 2-way speaker pair with mount, 8" woofers and 80 W RMS

The article is no longer in our assortment.

Features:

- Dedicated PA speaker system for fixed installations
- 2-way bass-reflex system for powerful bass
- 20 cm woofer (8") and 2.5 cm dome tweeter (1")
- 2-way tone control and level control
- Signal input and output via balanced XLR connectors
- White or titanium plastic housing (ABS) with metal grille
- Trapezoidal cabinet for corner installation
- Movable mounting bracket for ceiling or wall installation
- Ideal for PA applications in restaurants, bars, discos, shops, conferences, etc.
- With mounting bracket

Power supply:

Power consumption:

Technical specifications:

 Power:
 Program: 125W Rated: 80W RMS

 Frequency range:
 50 - 20000 Hz

 Sensitivity:
 90 dB (1W/1m)

230 V AC, 50 Hz

125 W

(provided)

Logistic

EAN / GTIN: 4026397356410 Weight: 17,45 kg Length: 0.58 m Width: 0.32 m Heigth: 0.43 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.


Mains input via IEC connector (M) mounting version power supply cord with safety plug











GTIN: 4026397356410

Attachment system:	Mounting bracket
Connections:	Input: line via 2 x 3-pin XLR
Speaker:	1 x woofer 8"
Color:	Black
Dimensions:	Width: 27 cm
	Depth: 24 cm
	Height: 36 cm
Weight:	15,55 kg
Components:	20 cm woofer (8"), 2.5 cm tweeter (1")
Input:	3-pin XLR
Output:	3-pin XLR
Sensitivity:	90 dB
Dimensions (H x W x D):	360 x 270 x 240 mm