

OMNITRONIC C-80A active white 2x

Active 2-way speaker pair with mount, 8" woofers and 80 W RMS

Art. No.: 11036725

GTIN: 4026397356427



The article is no longer in our assortment.

Features:

- Dedicated PA speaker system for fixed installations
- 2-way bass-reflex system for powerful bass
- 20 cm woofer (8") and 2.5 cm dome tweeter (1")
- 2-way tone control and level control
- Signal input and output via balanced XLR connectors
- White or titanium plastic housing (ABS) with metal grille
- Trapezoidal cabinet for corner installation
- Movable mounting bracket for ceiling or wall installation
- Ideal for PA applications in restaurants, bars, discos, shops, conferences, etc.
- With mounting bracket

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power:	Program: 125W Rated: 80W RMS
Frequency range:	50 - 20000 Hz
Sensitivity:	90 dB (1W/1m)
Attachment system:	Mounting bracket



EAN / GTIN: 4026397356427 Weight: 17,30 kg Length: 0.57 m Width: 0.33 m Heigth: 0.44 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Connections:	Input: line via 2 x 3-pin XLR
Speaker:	1 x woofer 8"
Color:	White
Dimensions:	Width: 27 cm
	Depth: 24 cm
	Height: 36 cm
Weight:	15,55 kg
Components:	20 cm woofer (8"), 2.5 cm tweeter (1")
Input:	3-pin XLR
Output:	3-pin XLR
Sensitivity:	90 dB