

OMNITRONIC DH-60A, active, white/set

Active speaker pair



The article is no longer in our assortment.

Features:

- Dedicated PA speaker system for fixed installations
- 2-way speaker system with 16.5 cm polypropylene woofer (6,5") and 2 cm dome tweeter (0.75") with horn front attachment
- Highly efficient bass-reflex system
- Well-balanced and clear sound, capable of high volumes
- 2-way tone control and level control
- Signal input and output via XLR connectors
- White or titanium plastic housing (ABS) with metal grille
- Delivery includes movable mounting bracket for ceiling or wall installation
- Ideal for PA applications in restaurants, bars, discos, shops, conferences, etc.

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	80,00 W
Frequency range:	55 - 20000 Hz
Dimensions:	Width: 20,8 cm
	Depth: 20,3 cm
	Height: 34,8 cm
Weight:	10,79 kg
Program power:	50 W



Logistic

EAN / GTIN: 4026397272239 Weight: 11,60 kg Length: 0.51 m Width: 0.23 m Heigth: 0.37 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Components:	16.5 cm woofer (6.5"), 2 cm horn (0.75")
Connection:	3-pin XLR
Maximum SPL:	103 dB
Impedance:	8 ohms
Dimensions (H x W x D):	348 x 208 x 203 mm