

OMNITRONIC OD-2 Wall Speaker 80hms black 2x

Speaker pair with mount, 2.5" full-range speakers and 15 W RMS







List price: 43.91 €

incl. 19% VAT.

Features:

- 8-ohm PA speaker system for general applications
- 1-way system with 30 W power
- 6.5 cm full-range speaker (2.5")
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles
- Black metal grille
- Scratchproof and shockproof
- Suitable for outdoor use IP44
- 2 pieces per set
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; product presentations and lectures

Package contents

- 2 x compact cabinet speaker, 2 x mounting material, 8 x screw, 1 x user manual

Technical specifications:

IP classification:	IP44
Power:	Program: 30W Rated: 15W RMS
Frequency range:	150 - 22000 Hz
Sensitivity:	88 dB
Max. SPL:	103 dB
Dispersion angle:	60° x 60°

Logistic

EAN / GTIN: 4026397543469 Weight: 1,12 kg Length: 0.29 m Width: 0.12 m Heigth: 0.12 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Impedance:	8 ohms
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles
Connections:	Input: speaker via spring terminal
Speaker:	1 x full range loudspeaker 2,5"
Material:	ABS Acrylonitrile butadiene styrene
Color:	Black, scratchproof and shockproof
Dimensions:	Width: 8,7 cm
	Depth: 11,1 cm
	Height: 9 cm
Weight:	1,01 kg