

OMNITRONIC OD-22T Wall Speaker 100V black

Universal wall speaker system with 2.5" full-range speakers and 15 W RMS

Art. No.: 11036908

GTIN: 4026397543520



List price: 47.48 €

incl. 19% VAT.

Description:

Universal wall speaker system

Use the OD-22T 100 V PA speaker by OMNITRONIC for sound reinforcement in restaurants, bars, shops or in your conference or recreation area.

The 2 x 6 cm full-range speaker feature a 3.5 x 6 cm passive membrane and a 100 V transformer. The attractive impact and scratch-resistant ABS plastic housing is equipped with a metal grille.

The stable mounting plate is equipped with a swivel and tilt joint, which allows wall and ceiling mounting at any angle.

Features:

- 100 V PA speaker system for general applications
- 2 x 6 cm full-range speaker (2 x 2.5")
- 3.5 x 6 cm passive membrane
- 100 V transformer
- Attractive ABS plastic cabinet (scratch-resistant) with metal grille
- Durable mounting plate with joint for panning and tilting allows ceiling or wall installation in most varying angles
- Spring clamps
- Ideal for PA applications in restaurants, bars, shops or conferences
- Suitable for outdoor use

Logistic

EAN / GTIN: 4026397543520

Weight: 1,24 kg

Length: 0.28 m

Width: 0.14 m

Height: 0.12 m

Technical specifications:

Power supply:	100 V DC
Rated power:	15 W RMS (8 ohms); 6 W RMS (100V PA)
Program power:	30 W
Frequency range:	120 - 22000 Hz
Sensitivity:	88 dB
Max. SPL:	95 dB
Dispersion angle:	60° x 60°
Impedance:	Public address systems 100V; 8 ohms
Connections:	Input: speakers via Spring terminal
Speakers:	1 x woofer (2.5") approx. 6.35 cm
Type of speaker:	Compact cabinet speaker
Dimensions:	Width: 20,9 cm Depth: 10,9 cm Height: 11 cm
Weight:	1,10 kg
