

## OMNITRONIC OD-22T Wall Speaker 100V black

2.5" full-range speaker, public address systems 100V, 20 W RMS

Art. No.: 11036908

GTIN: 4026397543520



### Description:

Universal wall speaker system

Use the OD-22T 100 V PA speaker by OMNITRONIC for sound reinforcement in restaurants, bars, shops or in your conference or recreation area.

The 2 x 6 cm full-range speaker feature a 3.5 x 6 cm passive membrane and a 100 V transformer. The attractive impact and scratch-resistant ABS plastic housing is equipped with a metal grille.

The stable mounting plate is equipped with a swivel and tilt joint, which allows wall and ceiling mounting at any angle.

### Features:

- 2 x 6 cm full-range speaker (2 x 2.5")
- 3.5 x 6 cm passive membrane
- Durable mounting plate with joint for panning and tilting allows ceiling or wall installation in most varying angles
- Scratchproof and shockproof
- Suitable for outdoor use
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; product presentations and lectures

### Logistic

EAN / GTIN: 4026397543520

Weight: 1,16 kg

Length: 0.28 m

Width: 0.14 m

Height: 0.12 m

## Technical specifications:

---

Power:	Program: 40W (8 ohms) Rated: 20W RMS (8 ohms) Rated: 6W RMS (100V PA)
Frequency range:	120 - 22000 Hz
Sensitivity:	88 dB
Max. SPL:	96 dB (100V PA); 104 dB (8 ohms)
Dispersion angle:	60° x 60°
Impedance:	Public address systems 100V; 8 ohms
Connections:	Input: speaker via spring terminal
Speaker:	2 x full range loudspeaker 2.5"
Type of speaker:	Compact cabinet speaker
Material:	ABS Acrylonitrile butadiene styrene
Color:	Black, scratchproof and shockproof
Dimensions:	Width: 20.9 cm Depth: 10.9 cm Height: 11 cm
Weight:	1.02 kg

## Scope of delivery:

---

1 x compact cabinet speaker  
1 x mounting material  
8 x screw  
1 x user manual