

OMNITRONIC OD-4T Wall Speaker 100V white 2x

Weather-proof wall speaker pair (IP65) with 4" woofers and 30 W RMS

Art. No.: 11036915 GTIN: 4026397543575









List price: 95.08 €

incl. 19% VAT.

Features:

- 2-way system with 10 cm woofer (4") and 1.3 cm tweeter (0.5")
- Durable plastic cabinet with metal grille and cover for the connectors
- Power selector switch with 8 ohms operating position
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles
- Suitable for outdoor use IP65
- 2 pieces per set
- White aluminum grille
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; product presentations and lectures

Package contents

- 2 x compact cabinet speaker, 2 x mounting bracket, 4 x knurled screw, 1 x user manual

Logistic

EAN / GTIN: 4026397543575

Weight: 3,72 kg Length: 0.33 m Width: 0.15 m Heigth: 0.21 m

Technical specifications:

| IP classification: | IP65 |
|--------------------|-----------------------------------|
| Power: | Program: 60W (8 ohms) |
| | Rated: 30W RMS (8 ohms) |
| | Rated: 16W RMS (100V PA) |
| Frequency range: | 100 - 20000 Hz |
| Sensitivity: | 88 dB |
| Max. SPL: | 100 dB (100V PA); 106 dB (8 ohms) |
| Dispersion angle: | 170° x 170° |

| Impedance: | Public address systems 100V; 8 ohms |
|--------------------|--|
| Housing color: | White |
| Attachment system: | Panning and tilting mounting bracket for ceiling or wall installation in most varying angles |
| Power tapping: | 2W; 4W; 8W; 16W RMS via selector switch switchable |
| Control elements: | Level control |
| Connections: | Input: speaker via screw terminal |
| Speaker: | 1 x woofer 4" 1 x dome tweeter 0,5" |
| Type of speaker: | Compact cabinet speaker |
| Dimensions: | Width: 12,5 cm |
| | Depth: 12,5 cm |
| | Height: 19,5 cm |
| Weight: | 3,45 kg |