

OMNITRONIC ODP-204T Installation Speaker 100V white 2x

2 weatherproof 4" wall speakers with mount, 10/20/40 W RMS

Art. No.: 11036953

GTIN: 4026397629712



List price: 224.91 €

incl. 19% VAT.

Description:

Great sound - also runs with 100 volts

You want reliable and balanced sound for your bar, restaurant, shop or the conference area of your hotel? You need indoor and outdoor speakers? With the OPD series you get powerful installation speakers that meets all your requirements.

The speakers have a brilliant sound pattern and are available in a low ohm (16 ohms) and in a 100 V version. These two cover both small and large installations. A rotatable mounting bracket is included in the delivery. A swivel wall mount with matching colors is optionally available.

With their weatherproofed (IP54) plastic cabinet the ODP speakers are well prepared for outdoor use, indoor use is of course also possible.

Features:

- 100 V PA speaker system for general applications
- 2-way system with 10 cm woofer (4") and 2 cm dome tweeter (0.8")
- Durable plastic cabinet with metal grille
- 100 V transformer with 3 power taps
- Power selector switch with 16 ohms operating position
- Swivel and tilting wall bracket for wall installation
- Screw plug terminal for easy handling
- With Mounting bracket
- Suitable for outdoor use
- 2 pieces per set
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; product presentations and lectures

Package contents

Logistic

EAN / GTIN: 4026397629712

Weight: 6,95 kg

Length: 0.42 m

Width: 0.20 m

Height: 0.30 m

- 1 x User manual, 2 x Top, 2 x Mounting bracket, 12 x Screw, 2 x Safety eyelet, 2 x Lid, 4 x Washers, 2 x Screwing, 2 x Screw terminal

Technical specifications:

IP classification:	IP65
Rated power:	40 W RMS (16 Ohm); 40 W RMS (100V PA)
Program power:	80 W
Frequency range:	75 - 20000 Hz
Sensitivity:	88 dB (1W/1m)
Max. SPL:	103 dB
Dispersion angle:	120° x 90°
Impedance:	Public address systems 100V; 16 ohms
Attachment system:	Mounting bracket
Power tapping:	10W; 20W; 40W RMS via Selector switch switchable
Connections:	Input: speaker via screw terminal
Speaker:	1 x woofer (4") approx. 10 cm Calottes highs (0.75") approx. 1.91 cm
Type of speaker:	Compact cabinet speaker; On-ceiling/on-wall speaker
Color:	White
Dimensions:	Width: 14,1 cm Depth: 17 cm Height: 23 cm
Weight:	6,35 kg