

## OMNITRONIC ODP-206 Installation Speaker 16 ohms black 2x

2 weather-proof 6" wall speakers (IP65) with mount, 80 W RMS

Art. No.: 11036954

GTIN: 4026397629729



**List price: 355.81 €**

incl. 19% VAT.

### Description:

Great sound - also runs with 100 volts

You want reliable and balanced sound for your bar, restaurant, shop or the conference area of your hotel? You need indoor and outdoor speakers? With the OPD series you get powerful installation speakers that meets all your requirements.

The speakers have a brilliant sound pattern and are available in a low ohm (16 ohms) and in a 100 V version. These two cover both small and large installations. A rotatable mounting bracket is included in the delivery. A swivel wall mount with matching colors is optionally available.

With their weatherproofed (IP65) plastic cabinet the ODP speakers are well prepared for outdoor use, indoor use is of course also possible.

### Features:

- 16-ohm PA speaker systems with an excellent sound for general applications
- 2-way system with 15 cm woofer (6") and 2.5 cm dome tweeter (1")
- Durable plastic cabinet with metal grille
- Screw plug terminal for easy handling
- With mounting bracket
- Black aluminum grille with acoustic foam
- Suitable for outdoor use IP65
- 2 pieces per set
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; product presentations and lectures

#### Package contents

- 2 x compact cabinet speaker, 2 x mounting bracket, 2 x lid, 2 x screwing, 4 x washer, 2 x screw plug-in terminal, 12 x screw, 2 x safety eyelet, 2 x gasket, 1 x user manual

### Logistic

EAN / GTIN: 4026397629729

Weight: 13,40 kg

Length: 0.53 m

Width: 0.25 m

Height: 0.42 m

## Technical specifications:

|                      |  |
|----------------------|--|
| IP classification:   | IP65   |
| Power:               | Program: 160W<br>Rated: 80W RMS  |
| Frequency range:     | 60 - 18000 Hz  |
| Sensitivity:         | 89 dB (1W/1m)  |
| Max. SPL:            | 110 dB   |
| Dispersion angle:    | 90° x 60°  |
| Impedance:           | 16 ohms  |
| Attachment system:   | Mounting bracket<br>1x M8 thread   |
| Connections:         | Speaker via screw plug-in terminal<br>Link: speaker via screw plug-in terminal   |
| Crossover frequency: | 2400 Hz  |
| Speaker:             | 1 x woofer 6"<br>Basket material: aluminum<br>Voice coil lows 1,5"<br>1 x dome tweeter 1"<br>Voice coil calotte tweeter 1" |
| Type of speaker:     | Compact cabinet speaker; on ceiling/on wall speaker  |
| Color:               | Black  |
| Dimensions:          | Width: 18,2 cm<br>Depth: 22,4 cm<br>Height: 36,2 cm  |
| Weight:              | 12,25 kg   |