

OMNITRONIC ODP-206T Installation Speaker 100V black 2x

2 weather-proof 6" wall speakers (IP65) with mount, 80 W RMS

Art. No.: 11036956 GTIN: 4026397629743





List price: 427.21 €

incl. 19% VAT.

Description:

Great sound - also runs with 100 volts

You want reliable and balanced sound for your bar, restaurant, shop or the conference area of your hotel? You need indoor and outdoor speakers? With the OPD series you get powerful installation speakers that meets all your requirements.

The speakers have a brilliant sound pattern and are available in a low ohm (16 ohms) and in a 100 V version. These two cover both small and large installations. A rotatable mounting bracket is included in the delivery. A swivel wall mount with matching colors is optionally available.

With their weatherproofed (IP65) plastic cabinet the ODP speakers are well prepared for outdoor use, indoor use is of course also possible.

Features:

- 2-way system with 15 cm woofer (6") and 2.5 cm dome tweeter (1")
- Durable plastic cabinet with metal grille
- Power selector switch with 16 ohms operating position
- Screw plug terminal for easy handling
- With mounting bracket
- Suitable for outdoor use IP65
- 2 pieces per set
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; product
 presentations and lectures
- Black aluminum grille
- Package contents
- 1 x user manual, 2 x top, 2 x mounting bracket, 12 x screw, 2 x safety eyelet, 2 x lid, 4 x washer, 2 x screwing, 2 x screw plug-in terminal, 2 x gasket

Logistic

EAN / GTIN: 4026397629743 Weight: 15,25 kg Length: 0.53 m Width: 0.25 m Heigth: 0.42 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

•	
IP classification:	IP65
Power:	Program: 160W
	Rated: 80W RMS
Frequency range:	60 - 18000 Hz
Sensitivity:	89 dB (1W/1m)
Max. SPL:	110 dB
Dispersion angle:	90° x 60°
Impedance:	Public address systems 100V; 16 ohms
Attachment system:	Mounting bracket
	2x M8 thread
Power tapping:	20W; 40W; 80W RMS via selector switch switchable
Connections:	Input: speaker via screw plug-in terminal
	Link: speaker via screw plug-in terminal
Crossover frequency:	2400 Hz
Speaker:	1 x woofer 6"
	Voice coil lows 1,5"
	1 x dome tweeter 1"
	Voice coil calotte tweeter 1"
Type of speaker:	Compact cabinet speaker; on ceiling/on wall speaker
Material:	Plastic
Color:	Black
Dimensions:	Width: 18,2 cm
	Depth: 22,4 cm
	Height: 36,2 cm
Weight:	14,15 kg