

OMNITRONIC ODX-208T Installation Speaker 100V white

Weather-proof 8" wall speaker (IP56) with mount, 150 W RMS









List price: 415.31 €

incl. 19% VAT.

Features:

- 2-way coaxial system with 20 cm woofer (8") and 2.5 cm dome tweeter (1")
- Durable plastic cabinet with metal grille
- Power selector switch with 8 ohms operating position
- Screw terminals for parallel connection
- With mounting bracket
- Suitable for outdoor use IP56
- Grey aluminum grille
- For application areas such as: Installation; sports centres/gyms; multi-purpose hall
 Package contents
- 1 x top, 1 x mounting bracket, 1 x user manual, 6 x screw, 1 x safety eyelet, 1 x lid, 2 x washer

Technical specifications:

IP classification:	IP56
Power:	Program: 300W Rated: 150W RMS
Frequency range:	80 - 18000 Hz
Sensitivity:	96 dB (1W/1m)
Max. SPL:	117 dB
Dispersion angle:	100° x 100°
Impedance:	8 ohms; public address systems 100V

Logistic

EAN / GTIN: 4026397723014 Weight: 12,00 kg Length: 0.36 m Width: 0.33 m Heigth: 0.34 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Attachment system:	Mounting bracket
Power tapping:	37,5W; 75W; 150W RMS via selector switch switchable
Connections:	Input: speaker via screw terminal
Crossover frequency:	2500 Hz
Speaker:	1 x woofer 8" Basket material: aluminum
	Voice coil lows 2"
	1 x compression tweeter highs 1"
	Voice coil compression tweeter highs 1,4"
Type of speaker:	On ceiling/on wall speaker
Color:	White
Dimensions:	Width: 35 cm
	Depth: 30,8 cm
	Height: 31 cm
Weight:	10,85 kg