

OMNITRONIC ODX-215TL Installation Speaker 100V light gray

Weather-proof 15" wall speaker (IP56) with mount, 400 W RMS

Art. No.: 11036969

GTIN: 4026397703238



Features:

- 2-way coaxial system with 38 cm woofer (15") and 3.6 cm tweeter (1.4")
- Durable plastic cabinet with metal grille
- Power selector switch with 8 ohms operating position
- Screw terminals for parallel connection
- With mounting bracket
- Grey aluminum grille with acoustic foam
- Suitable for outdoor use IP56
- For application areas such as: Installation; sports centres/gyms; multi-purpose hall

Logistic

EAN / GTIN: 4026397703238

Weight: 35,30 kg

Length: 0.61 m

Width: 0.57 m

Height: 0.59 m

Bulky product

Technical specifications:

IP classification:	IP56
Power:	Program: 800W Rated: 400W RMS
Frequency range:	50 - 18000 Hz
Sensitivity:	103 dB (1W/1m)
Max. SPL:	129 dB
Dispersion angle:	60° x 25°
Impedance:	8 ohms; public address systems 100V
Attachment system:	Mounting bracket

Power tapping:	75W; 150W; 300W; 400W RMS via selector switch switchable
Connections:	Input: speaker via screw terminal
Crossover frequency:	1500 Hz
Speaker:	1 x woofer 15" Voice coil lows 3" 1 x compression tweeter highs 1.4" Voice coil compression tweeter highs 3"
Type of speaker:	On ceiling/on wall speaker
Color:	Light gray
Dimensions:	Width: 49 cm Depth: 52 cm Height: 50 cm
Weight:	32.15 kg

Scope of delivery:

- 1 x top
- 1 x mounting bracket
- 1 x user manual
- 6 x screw
- 1 x safety eyelet
- 1 x lid
- 8 x washer
- 1 x screwing