

OMNITRONIC ODX-215TL Installation Speaker 100V white

Weather-proof 15" wall speaker (IP56) with mount, 400 W RMS









List price: 1046.01 €

incl. 19% VAT.

Features:

- 2-way coaxial system with 38 cm woofer (15") and 3.6 cm tweeter (1.4")
- Durable plastic cabinet with metal grille
- Power selector switch with 8 ohms operating position
- Screw terminals for parallel connection
- With mounting bracket
- Grey aluminum grille with acoustic foam
- Suitable for outdoor use IP56
- For application areas such as: Installation; sports centres/gyms; multi-purpose hall
 Package contents
- 1 x top, 1 x mounting bracket, 1 x user manual, 6 x screw, 1 x safety eyelet, 1 x lid, 8 x washer, 1 x screwing

Technical specifications:

Program: 800W Rated: 400W RMS 50 - 18000 Hz
50 18000 Hz
50 - 18000 HZ
103 dB (1W/1m)
129 dB
60° x 25°
8 ohms; public address systems 100V

Logistic

EAN / GTIN: 4026397703238 Weight: 35,30 kg Length: 0.61 m Width: 0.57 m Heigth: 0.59 m Bulky product

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Attachment system:	Mounting bracket
Power tapping:	75W; 150W; 300W; 400W RMS via selector switch switchable
Connections:	Input: speaker via screw terminal
Crossover frequency:	1500 Hz
Speaker:	1 x woofer 15"
	Voice coil lows 3"
	1 x compression tweeter highs 1,4"
	Voice coil compression tweeter highs 3"
Type of speaker:	On ceiling/on wall speaker
Color:	Grey
Dimensions:	Width: 49 cm
	Depth: 52 cm
	Height: 50 cm
Weight:	32,15 kg