

OMNITRONIC ODX-206T Installation Speaker 100V white

Weather-proof 6.5" wall speaker (IP56) with mount, 100 W RMS

Art. No.: 11036972

GTIN: 4026397721515



Features:

- 2-way coaxial system
- Durable plastic cabinet with metal grille
- Power selector switch with 8 ohms operating position
- Screw terminals for parallel connection
- With mounting bracket
- White metal grille
- Suitable for outdoor use IP56
- For application areas such as: Installation; sports centres/gyms; multi-purpose hall

Logistic

EAN / GTIN: 4026397721515

Weight: 8,20 kg

Length: 0.33 m

Width: 0.33 m

Height: 0.30 m

Technical specifications:

IP classification:	IP56
Power:	Program: 200W (8 ohms) Rated: 100W RMS (8 ohms)
Frequency range:	100 - 18000 Hz
Sensitivity:	93 dB (1W/1m)
Max. SPL:	116 dB
Dispersion angle:	100° x 100° conical
Impedance:	8 ohms; public address systems 100V
Attachment system:	Mounting bracket

Power tapping:	25W; 50W; 100W RMS via selector switch switchable
Connections:	Screw terminal
Crossover frequency:	2800 Hz
Speaker:	1 x woofer 6.5" with ferrit magnet Voice coil lows 1.4" 1 x compression tweeter highs 0.8" Voice coil compression tweeter highs 1"
Type of speaker:	On ceiling/on wall speaker
Type of construction:	Vented
Color:	White
Dimensions:	Width: 25.65 cm Depth: 27.3 cm Height: 25.85 cm
Weight:	7.20 kg

Scope of delivery:

- 1 x user manual
- 1 x top
- 1 x mounting bracket
- 5 x screw
- 1 x safety eyelet
- 1 x lid
- 2 x washer
- 1 x screwing