

OMNITRONIC M-1220 Monitor 600W

2-way stage monitor with 12" woofers and 600 W power









List price: 129.71 €

incl. 19% VAT.

Features:

- Rugged 2-way speaker-system in a stable wooden housing
- Large mid-range horn with coil-driver for balanced mids
- With passive 2-way crossover
- Powerful, dry bass via voluminous housing and bass-reflex tubes
- Very high durability
- Scratch-resistant, black felt-covering
- With stable protective steel corners
- Black metal grille
- 2 recessed carrying handles
- Application possibility: Standing; monitoring
- For further information about this product, please refer to the Data Sheet under "Downloads" Package contents
- 1 x user manual, 1 x compact cabinet speaker, 4 x foot, 4 x screw

Technical specifications:

Power:	Program: 600W Rated: 300W RMS
Frequency range:	40 - 18000 Hz
Sensitivity:	96 dB
Impedance:	8 ohms
Attachment system:	Flange: Ø 35mm

Logistic

EAN / GTIN: 4026397101188 Weight: 12,65 kg Length: 0.41 m Width: 0.32 m Heigth: 0.65 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Connections:	Speaker via 2 x speaker built-in socket (F)
Speaker:	1 x woofer 12"
	Basket material: steel
	Conematerial: cardboard/paper
Type of speaker:	Stage monitor
Recessed carrying handle:	2 pc/pcs
Material:	, 15 mm
Color:	Black
Dimensions:	Width: 61,5 cm
	Depth: 27,5 cm
	Height: 39,5 cm
Weight:	11,65 kg