

OMNITRONIC M-1530 Monitor 800W

2-way stage monitor









The article is no longer in our assortment.

Features:

- Rugged 2-way speaker-system in a stable wooden housing
- Large mid-range horn with coil-driver for balanced mids
- With passive 2-way crossover
- Powerful, dry bass via voluminous housing and bass-reflex tubes
- Vertical loudspeaker alignment
- Very high durability
- Scratch-resistant, black felt-covering
- Strong protective grille for perfect protection
- With stable protective steel corners

Technical specifications:

Power:	Program: 800W Rated: 400W RMS
Frequency range:	30 - 18000 Hz
Impedance:	8 ohms
Speaker:	1 x woofer 15"
Type of speaker:	Stage monitor
Dimensions:	Width: 66,5 cm
	Depth: 48 cm
	Height: 47,5 cm

Logistic

EAN / GTIN: 4026397196009 Weight: 18,25 kg Length: 0.68 m Width: 0.53 m Heigth: 0.50 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Weight:	16,50 kg
Components:	38 cm woofer (15"), horn
Connection:	2 Speaker sockets
Sensitivity:	97 dB
Impedance:	8 ohms
Dimensions (H x W x D):	665 x 480 x 475 mm