

OMNITRONIC SM-212A Active Stage Monitor

Active 2-way stage monitor 200 W











The article is no longer in our assortment.

Features:

- Active pro stage monitor for live and playback applications
- 2-way system, 200 W max.
- 30 cm subwoofer (12") in bass-reflex cabinet provides deep bass and high SPL
- 8 cm titanium driver system (3.2") for exceptional high frequencies
- Adjustable feedback filter
- Low-noise mic and line input (XLR/6.3 mm jack) with volume control
- 3-band EQ
- Master control with clip LED
- Parallel output (XLR/6.3 mm jack) for linking further active speaker systems
- Strap handle
- Rugged wooden housing with protective steel corners and scratch-resistant, black felt-covering
- Impact-resistant steel grille

Technical specifications:

Power supply:	230 V AC, 50 Hz
Frequency range:	50 - 20000 Hz
Dimensions:	Width: 41,2 cm
	Depth: 56 cm
	Height: 35,7 cm
Weight:	15,55 kg
Rated power:	100 W RMS

Logistic

EAN / GTIN: 4026397482911 Weight: 19,20 kg Length: 0.64 m Width: 0.45 m Heigth: 0.50 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Program power:	200 W
Components:	30 cm woofer (12"), 8 cm horn (3.2")
Line input:	6.3 mm jack with parallel output
Microphone input:	3-pin XLR with parallel output
Dimensions (H x W x D):	412 x 560 x 357 mm