

OMNITRONIC KM-110A Active Stage Monitor, coaxial

Monitor, 10" woofer, 1.35" driver, 150 W RMS LF, 50 W RMS HF

Art. No.: 11038035

GTIN: 4026397529883



Features:

- Active 2-way coaxial stage monitor for live and playback applications
- Class D/AB biamp power amplifier
- 25 cm bass speaker (10") and 3.5 cm compression driver (1.35")
- Bassreflex cabinet provides deep bass and high SPL
- Low cut, volume control
- Black metal grille
- 2 recessed carrying handles
- For application areas such as: Stage; band/rehearsal room; mobile use

Logistic

EAN / GTIN: 4026397529883

Weight: 15,85 kg

Length: 0.46 m

Width: 0.41 m

Height: 0.54 m

Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	80 W 1/8 power
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 2 A fuse replaceable
Power:	Program: 300W Rated: 50W RMS HF Rated: 150W RMS LF

Frequency range:	60 - 20000 Hz
Max. SPL:	121 dB
Dispersion angle:	80° x 80°
Attachment system:	Flange:
Control elements:	Power switch, level control, tone control, groundlift selector
Controls:	Overload; limiter
Status LED:	Power, signal, limit
Connections:	Input: line via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Output: line via 1 x 3-pin XLR
Input channels:	1 x mono via XLR or jack, channel control via rotary dial
Speaker:	1 x woofer 10" with ferrit magnet Basket material: steel Conematerial: cardboard/paper 1 x voice coil compression tweeter highs 1.35"
Type of speaker:	Compact cabinet speaker; coaxial speaker; stage monitor
Recessed carrying handle:	2 pc/pcs
Material:	MDF (medium density fiberboard), 15 mm
Color:	Black, textured coating, painted
Dimensions:	Width: 48 cm Depth: 30 cm Height: 42 cm
Weight:	14.30 kg

Scope of delivery:

- 1 x compact cabinet speaker
- 1 x user manual
- 1 x power cord