

OMNITRONIC KM-112A Active Stage Monitor, coaxial

Monitor, 12" woofer, 1,35" driver, LF: 250 W RMS, HF: 50 W RMS

Art. No.: 11038036

GTIN: 4026397529890



List price: 379.61 €

incl. 19% VAT.

Features:

- Active 2-way coaxial stage monitor for live and playback applications
- Class D/AB biamp power amplifier
- Power output LF: 250 W RMS
- Power output HF: 50 W RMS
- 30 cm bass speaker (12") and 3.5 cm compression driver (1.35")
- 80° x 80° nominal coverage
- Bassreflex cabinet provides deep bass and high SPL
- Line input (XLR/6.3 mm jack)
- Parallel output (XLR) for linking further active speaker systems
- Low cut, volume control
- Dual limiter and overload protection
- Rugged MDF housing with scratch-resistant lacquer surface and impact-resistant steel grille
- Flange for stand installation

Logistic

EAN / GTIN: 4026397529890

Weight: 18,70 kg

Length: 0.53 m

Width: 0.46 m

Height: 0.57 m

Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	180 W
Power connection:	Mains input IEC connector (M) mounting version Power supply cord with safety plug (provided)
Rated power:	250 W RMS LF; 50 W RMS HF
Program power:	500 W

Frequency range:	50 - 20000 Hz
Max. SPL:	123 dB
Dispersion angle:	80° x 80°
Connections:	Input: 1 x line via 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Output: 1 x line via 3-pin XLR
Input channels:	1 x mono via XLR or jack, channel control via Rotary dial
Speakers:	1 x woofer (12") approx 30 cm with ferrit magnet 1 x Voice coil compression tweeter highs (1.35") approx 3,5cm
Type of speaker:	Compact cabinet speaker; Coaxial speaker; stage monitor
Dimensions:	Width: 50 cm Depth: 34 cm Height: 46 cm
Weight:	16,70 kg