

OMNITRONIC KM-115A Active Stage Monitor coaxial

Monitor, 15" woofer, 1.35" driver, 250 W RMS LF, 50 W RMS HF

Art. No.: 11038037

GTIN: 4026397529906



Features:

- Active 2-way coaxial stage monitor for live and playback applications
- Class D/AB biamp power amplifier
- 38 cm bass speaker (15") and 3.5 cm compression driver (1.35")
- Bassreflex cabinet provides deep bass and high SPL
- Low cut, volume control
- Black metal grille
- Application possibility: Standing; monitoring; on stand
- For application areas such as: Band/rehearsal room; mobile use; stage

Logistic

EAN / GTIN: 4026397529906

Weight: 25,20 kg

Length: 0.57 m

Width: 0.49 m

Height: 0.67 m

Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	300 W 1/8 power
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 2 A fuse replaceable
Power:	Program: 500W Rated: 50W RMS HF Rated: 250W RMS LF

Frequency range:	45 - 20000 Hz
Max. SPL:	124 dB
Dispersion angle:	60° x 60°
Attachment system:	Flange: Ø 35mm
Control elements:	Power switch, level control, tone control, groundlift selector
Controls:	Overload; limiter
Status LED:	Power, limit
Connections:	Input: line via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Output: line via 1 x 3-pin XLR
Input channels:	1 x mono via XLR or jack, channel control via rotary dial
Speaker:	1 x woofer 15" with ferrit magnet Basket material: steel Conematerial: cardboard/paper 1 x voice coil compression tweeter highs 1.35"
Type of speaker:	Compact cabinet speaker; coaxial speaker; stage monitor
Material:	MDF (medium density fiberboard), 15 mm
Color:	Black, textured coating, painted
Dimensions:	Width: 60 cm Depth: 37 cm Height: 54 cm
Weight:	22.90 kg

Scope of delivery:

- 1 x compact cabinet speaker
- 1 x user manual
- 1 x power cord