

OMNITRONIC KM-115 Stage Monitor, coaxial

Monitor, 15" woofer, 1.35" driver, 250 W RMS / 8 ohms









The article is no longer in our assortment.

Features:

- Passive coaxial stage monitor for live and playback applications
- 38 cm bass speaker (15") and 3.5 cm compression driver (1.35")
- 60° x 60° nominal coverage
- Bassreflex cabinet provides deep bass and high SPL
- Rugged MDF housing with scratch-resistant lacquer surface and impact-resistant steel grille
- Flange for stand installation

Technical specifications:

Power:	Program: 500W Rated: 250W RMS
Frequency range:	53 - 18000 Hz
Max. SPL:	123 dB
Impedance:	8 ohms
Speaker:	1 x woofer 15"
Type of speaker:	Stage monitor
Dimensions:	Width: 60 cm
	Depth: 37 cm
	Height: 54 cm
Weight:	21,80 kg

Logistic

EAN / GTIN: 4026397580716 Weight: 24,20 kg Length: 0.58 m Width: 0.48 m Heigth: 0.68 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Components:	38 cm woofer (15"), 3.5 cm driver (1.35")
Connection:	2 Speaker sockets
Impedance:	8 ohms
Dispersion angle:	60° x 60°