

OMNITRONIC KB-210A Plastic cab., active

Active 2-way speaker system for PA and DJ applications

Art. No.: 11038694 GTIN: 4026397425284



The article is no longer in our assortment.

Features:

- Active speaker-system for direct connection with the signal source
- Large mid-range horn
- 2-way crossover
- Mic and line inputs with separate level controls
- Master control with 2-way tone control and clip LED
- Line output for linking further active speaker systems
- Delivery includes brackets for use as floor monitor
- Strong protective grille for perfect protection
- Flange for stand installation
- Carrying handles
- Scratch-resistant plastic housing
- Compact speaker-system for car transport
- Ideal for live music or for permanent installation in party rooms

Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz
Output power:	Max. 240 W
Frequency range:	55 - 18000 Hz
Dimensions:	Width: 51 cm
	Depth: 35 cm
	Height: 28,5 cm

Logistic

EAN / GTIN: 4026397425284 Weight: 14,70 kg Length: 0.41 m Width: 0.34 m Heigth: 0.57 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Weight:	13,35 kg
Rated power:	120 W RMS
Program power:	240 W
Components:	25 cm woofer (10"), 3.5 cm horn (1.35")
Inputs:	
Mic:	3-pin XLR or 6.3 mm jack, bal.
Line:	3-pin XLR, bal. or stereo RCA
Outputs:	
Line:	3-pin XLR or 6.3 mm jack, bal.
Maximum SPL:	110 dB
Dimensions (H x W x D):	510 x 350 x 285 mmm