OMNITRONIC KPA-215A PA Cabinet active

Active 2-way speaker-system

Art. No.: 11038722

GTIN: 4026397200799

Features:

- XLR and jack socket for direct connection with the signal source (line, mic)
- Line/Mic pad for input level adjustment
- Large mid-range horn with powerful driver
- Bi-amped for cristal clear playback
- Ideal as floor-monitor, standing, on a speaker stand or on a wall-mounting
- Strong protective grille for perfect protection
- Scratch-resistant plastic housing
- Compact speaker system for car transport
- Ideal for live music or discotheques
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4026397200799
Weight: 25,10 kg
Length: 0.55 m
Width: 0.41 m
Heigth: 0.76 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	510.00 W
Output power:	Max. 510 W
Frequency range:	55 - 18000 Hz
Dimensions:	Width: 50 cm Depth: 36 cm Height: 73 cm
Weight:	22.80 kg

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Dimensions (H x W x D):	730 x 500 x 360 mm
Speaker-system:	
Rated power:	250 W RMS
Program power:	500 W
Components:	38 cm woofer (15"), 2.5 cm horn (1")
Inputs:	XLR/jack
Dispersion angle:	90° x 40°
Maximum SPL:	120 dB
Impedance:	8 ohms
LF-amplifier:	
Maximum power output:	450 W / 4 ohms
Distortion:	0.1 %
HF-amplifier:	
Maximum power output:	50 W / 4 ohms
Distortion:	0.1 %

Scope of delivery:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.