

OMNITRONIC XKB-210A 2-way Speaker, active, Bluetooth

Active speaker with 10" woofer, 1.35" driver, 75 W RMS HF, 175 W RMS LF

Art. No.: 11038794

GTIN: 4026397628340



Description:

The speaker systems of the XKB series are high-performance active speaker systems in light-weight and rugged plastic cabinets. They can be flexibly used for permanent installations and professional live applications. The 2-way speaker systems are designed as full-range bass-reflex systems with separate power amplifiers for the high-frequency range and the low-frequency range featuring inputs for microphones and line sources and parallel outputs for coupling with other active speakers. The DSP (digital signal processor) features convenient application presets for quick sound contouring (models XKB-212A and XKB-215). The built-in Bluetooth player allows for streaming music wirelessly from smartphones or tablets via Bluetooth. The speakers systems are protected through limiters and extensive protective circuits. The enclosure offers multiple setup options (use as a floor monitor, wall or stand mounting).

Features:

- Active PA speaker system for touring applications and permanent installations
- Class D biamp amplifier (LF 175 W, HF 75 W)
- 2-way bass-reflex enclosure with 25 cm woofer and 3.5 cm driver
- 1 mic/line combo input (XLR/jack) with level control
- 1 line input (XLR/RCA) with level control
- Master control with 2-band EQ
- The device is cooled by cooling fan
- Control via Bluetooth
- Black metal grille with acoustic foam
- 3 Rugged carrying handles
- For application areas such as: Party room; mobile use; mobile djs / entertainer; small rental
- Application possibility: Standing; monitoring; on stand

Logistic

EAN / GTIN: 4026397628340

Weight: 12,45 kg

Length: 0.58 m

Width: 0.36 m

Height: 0.37 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	550 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power:	Program: 350W Rated: 75W RMS HF Rated: 175W RMS LF
Frequency range:	65 - 20000 Hz
Sensitivity:	95 dB
Dispersion angle:	90° x 50°
Cooling:	Cooling fan
Control:	Bluetooth
Bluetooth device name:	Omnitronic XKB
Attachment system:	Flange: Ø 35mm
Circuitry:	Class D Biamp
Control elements:	Power switch, Input sensitivity switch, level control per channel, connect, tone control
Controls:	Limiter
Status LED:	Power, signal, limit, pairing
Connections:	Output: line via 1 x 3-pin XLR Input: line via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: line via 1 x stereo RCA Input: line via 1 x 3-pin XLR
Input channels:	1 x mono via XLR or RCA or bluetooth, channel control via rotary dial 1 x mono with mic-line switch via Combination socket (XLR/jack), channel control via rotary dial
Equalizer:	Master: 1 x 2-band tone control
Speaker:	1 x woofer 10" with ferrit magnet Basket material: steel Conematerial: cardboard/paper Voice coil lows 1,5" Voice coil compression tweeter highs 1.35"
Type of speaker:	Compact cabinet speaker
Carrying handle:	3 pc/pcs
Material:	Plastic
Color:	Black
Dimensions:	Width: 31 cm Depth: 32 cm Height: 48 cm
Weight:	11.15 kg

Scope of delivery:

- 1 x compact cabinet speaker
- 1 x user manual
- 1 x power cord
- 1 x declaration of conformity