

OMNITRONIC XKB-212A 2-Way Speaker, active, DSP

Active speaker with 12" woofer, 1,35" driver, LF: 300 W RMS, HF: 60 W RMS

Art. No.: 11038795

GTIN: 4026397606485



List price: 367.71 €

incl. 19% VAT.

Features:

- Active 12/2 full range system for mobile live and DJ applications
- DSP-controlled biamp amplifier (LF class D, HF class A/B)
- Application presets for quick sound contouring:
 - LIVE (linear adjustment)
 - MUSIC (slight low and high frequency boost)
 - SPEECH (optimized speech intelligibility)
 - DJ (increased presence and bass)
- TRIPOD (for stand mounting)
- MONITOR (for use as a floor monitor)
- WALL (for wall mounting)
- 24-bit DSP with adjustable high-pass filter, parametric 3-band EQ and signal delay
- Built-in Bluetooth player for audio streaming from compatible Bluetooth devices such as smartphones, tablets and notebooks
- 2-way bass-reflex enclosure with 30 cm woofer and 3.5 cm titanium driver
- 2 mic/line inputs (XLR/6.3 mm jack) with separate level controls
- Parallel XLR output for linking further active speaker systems
- Limiter for overload protection
- Master volume/DSP push control
- Power, signal and limit LED
- Light-weight plastic cabinet with metal grille and carrying handles
- 36 mm flange for stand installation
- Applications: standing, as floor monitor, on a speaker stand or wall holder
- Controlling by Bluetooth
- LCD display for easy controlling

Logistic

EAN / GTIN: 4026397606485

Weight: 16,85 kg

Length: 0.44 m

Width: 0.40 m

Height: 0.68 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Rated power:	300 W RMS LF; 60 W RMS HF
Program power:	600 W
Frequency range:	55 - 20000 Hz
Sensitivity:	95 dB
Control:	Bluetooth
Attachment system:	Ø 35mm
Circuitry:	Class D Biamp
Display type:	LCD display
Equalizer:	Master: 1 x 3-band tone control
Connections:	Output: line via 1 x 3-pin XLR
Input channels:	2 x mono with Mic-line switch via 3-pin XLR/6.35mm jack (F) combination socket (mounting version), channel control via Rotary dial
Speakers:	1 x woofer (12") approx. 30 cm Voice coil lows (2.4") approx. 6.10 cm with ferrit magnet Voice coil compression tweeter highs (1.35") approx. 3,5 cm
Type of speaker:	Compact cabinet speaker
Type:	Vented
Dimensions:	Width: 38 cm Depth: 35 cm Height: 61 cm
Weight:	15,45 kg