

OMNITRONIC AS-360 Active system

Active complete system, 360 W RMS

Art. No.: 11038802

GTIN: 4026397357493



The article is no longer in our assortment.

Features:

- Two-way satellite system consisting of two tops and one subwoofer
- Perfectly tuned system for demanding home users, DJs, musicians, small parties etc.
- Easy-to-use complete system
- Rugged full-range top speaker in a stable wooden housing
- Tops: with passive 2-way crossover
- Sub: powerful, dry bass via optimized double vented bandpass system
- Balanced frequency range with high sound pressure
- Speaker connection via lockable Speaker-plugs
- Scratch-resistant lacquer surface
- Compact speaker system for car transport

Logistic

EAN / GTIN: 4026397357493

Weight: 29,20 kg

Length: 0.48 m

Width: 0.41 m

Height: 0.64 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
---------------	-----------------

Power consumption:	500,00 W
--------------------	----------

Output power:	Max. 360 W
---------------	------------

Frequency range:	120 - 20000 Hz
------------------	----------------

Dimensions:	Width: 35 cm
	Depth: 14,5 cm
	Height: 17 cm

Weight:	26,65 kg
---------	----------

Top:

Rated power:	120 W RMS
Program power:	180 W
Components:	2 x 10 cm woofer (2 x 4"), dome tweeter
Connection:	1 Speaker socket
Sensitivity:	90 dB
Maximum SPL:	108 dB
Impedance:	4 ohms
Dispersion angle:	60° x 60°
Crossover frequency:	3 kHz
Dimensions (H x W x D):	350 x 145 x 170 mm
Subwoofer:	
Rated power:	140 W RMS
Program power:	200 W
Components:	20 cm woofer (8")
Sensitivity:	96 dB
Maximum SPL:	114 dB
Impedance:	4 ohms
Dimensions (H x W x D):	430 x 320 x 420 mm
Amplifier:	
Total power output:	360 W RMS
Nominal power output satellite:	2 x 120 W RMS
Nominal power output subwoofer:	120 W RMS
Active crossover:	
Crossover frequency:	140 Hz
Inputs:	2 x XLR, 2 x RCA
Outputs:	2 Speaker sockets
Min. input sensitivity:	0.350 V
Control elements:	Power switch, Gain control , Sublevel control
LED indicators (per channel):	Power
Protection circuits:	Short-circuit