

OMNITRONIC MAXX-1000DSP MK2 2.1 Active System

Powerful active PA (15" sub, 8" tops) with DSP, 1000 watts

Art. No.: 11038826

GTIN:



The article is no longer in our assortment.

Features:

- Mobile 2.1 system with DSP and 1000 watts RMS power
- Provides perfect sound and good level stability in various kinds of mobile PA applications up to medium-sized party events - ideal for solo entertainers, bands and mobile discos
- 38 cm subwoofer (15") in bassreflex cabinet provides powerful, dry bass
- Two satellites with 20 cm bass-midrange speakers (8") and 3.5 cm driver system (1.4")
- Satellites with passive 2-way crossover, PTC tweeter protection
- Balanced signal input XLR/6.3 mm jack L/R, with level switch
- Additional stereo RCA input
- Parallel XLR line output L/R
- 5 EQ presets with indicators, DSP-controlled
- Signal limiter, DSP-controlled
- Separate volume control for subwoofer and satellites
- Adjustable crossover frequency 80-200 Hz
- Stereo/mono selection
- Subwoofer with plywood enclosure
- Satellites with MDF enclosure
- Enclosure (15 mm) with scratch-resistant lacquer surface, steel grille and flange
- Subwoofer with M20 metal flange for mounting a satellite speaker
- 4 castors, 2 of which with locking brakes
- Delivery includes two speaker cables
- Digital signal processor

bass

- Castors

Package contents

- 1 x bass, 1 x top, 1 x user manual, 2 x speaker cable, 1 x power cord

Logistic

Technical specifications:

Power consumption:	280 W 1/8 power
Frequency range:	80 - 19000 Hz top 45 - 150 Hz bass
DSP:	Digital signal processor
Circuitry:	Class D
Weight:	55,55 kg
Bass	
Sensitivity:	97 dB
Max. SPL:	126 dB
Speaker:	1 x woofer 15"
Type of speaker:	Subwoofer
Type of construction:	Vented
Transport aid:	Castors
Dimensions:	Width: 47,6 cm Depth: 70 cm Height: 53 cm
Weight:	35 kg
Top	
Sensitivity:	95 dB
Max. SPL:	121 dB
Type of speaker:	Compact cabinet speaker
Dimensions:	Width: 26,6 cm Depth: 24 cm Height: 41,5 cm
Weight:	10 kg
Power supply:	230 V AC, 50 Hz
Amplifier power:	LF 600 W RMS + HF 2 x 200 W RMS
Components:	
Subwoofer:	38 cm woofer (15")
Satellite speakers:	20 cm woofer (8"), 3.6 cm driver (1.4")
Dispersion angle:	50-100° x 55°
Connection:	
Line input:	combination XLR/6.3 mm jack L/R, RCA L/R
Parallel output:	XLR L/R
Satellite:	Speaker L/R
Dimensions (L x W x H):	
Subwoofer:	700 x 476 x 530 mm
Satellite speakers:	240 x 266 x 415 mm
Subwoofer:	35 kg
Satellite speakers:	10 kg

OMNITRONIC MAXX 2.1DSP Satellite 2x

Attachment system:

Ø 35mm
