

OMNITRONIC AR-212A Active 2-way speaker

Active 2-way speaker system for PA and DJ applications, 550 W max.

Art. No.: 11038840

GTIN: 4026397477764





The article is no longer in our assortment.

Features:

- Active full-range system with class D circuitry
- 2-channel power amplifier with integrated active crossover network
- 2-way system, 550 W max.
- 2 x 30 cm subwoofer in bassreflex cabinet
- 12 cm titanium driver system
- Mic and line inputs (XLR/6.3 mm jack) with separate level controls
- Master control with 2-band EQ
- Parallel line output for linking further active speaker systems
- Limiter and speaker switch-on delay
- MDF enclosure with scratch-resistant lacquer surface, impact-resistant steel grille
- Protection against short-circuit and overheat
- For mobile live and DJ applications

Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	650,00 W
Frequency range:	40 - 20000 Hz
Dimensions:	Width: 90 cm
	Depth: 41 cm
	Height: 38,5 cm
Weight:	34,80 kg

Logistic

EAN / GTIN: 4026397477764 Weight: 39,00 kg Length: 0.51 m Width: 0.46 m Heigth: 0.98 m Bulky product

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

LF amplifier:	500 W max.
HF amplifier:	50 W max.
Components:	2 x 30 cm woofer (12"), 11.5 cm horn (4.5")
Line input:	combination XLR/6.3 mm jack
Microphone input:	combination XLR/6.3 mm jack
Line output:	XLR (parallel output)
Dimensions (H x W x D):	900 x 410 x 385 mm