

OMNITRONIC BOB-82X Subwoofer white

Passive dual 8" subwoofer for the BOB series

Art. No.: 11038864 GTIN: 4026397658903



The article is no longer in our assortment.

Features:

- 2 x 8" bassreflex subwoofer
- 2 x 150 watt RMS rated power
- 125 dB maximum SPL
- Ideal bass addition for BOB satellite speakers
- Optimized for use with 4 satellites in combination with a 2-channel amplifier
- Frequency range: 50-200 Hz (-10 dB), integrated crossover network
- 2 x satellite speaker outputs with high-pass filter
- For application areas such as: Trade fair and shop fitting; home entertainment; product presentations and lectures
- 4 Rugged carrying handles Package contents
- 1 x user manual, 1 x bass

Technical specifications:

Power:	Program: 2x 300W Rated: 2x 150W RMS
Frequency range:	55 - 250 Hz
Sensitivity:	102 dB (1W/1m)
Max. SPL:	125 dB
Impedance:	8 ohms
Attachment system:	Flange: M20 thread

Logistic

EAN / GTIN: 4026397658903 Weight: 20,25 kg Length: 0.42 m Width: 0.33 m Heigth: 0.60 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Input: speaker via spring terminal
2 x woofer 8"
Voice coil lows 2"
Subwoofer
Vented
4 pc/pcs
MDF (medium density fiberboard), 15 mm
White, textured coating
Width: 26,5 cm
Depth: 36,1 cm
Height: 53,5 cm
19,30 kg