

## **OMNITRONIC BHD-01 Waist band amplifier**

Extremely compact 5 W waistband amplifier

### Art. No.: 11038881

GTIN: 4026397231632







# The article is no longer in our assortment.

#### Features:

- Waistband amplifier with active speaker and headset microphone
- Designed as girdle bag with adjustable snap-in strap
- A full success as ideal PA-system for professional promotion events "on the road" or for hobby promotion shows
- Ideal for all mains independent and wireless applications like seminars, conferences, presentations, tradeshows, fashion shows, solo entertainers, weddings, sales booths, aerobics etc.
- For voice amplification with up to 50 listeners
- With mic input and volume control
- Power supply via 6 optional mignon batteries (type AA) or rechargeable batteries
- Built-in battery charger
- Optional power unit for charging the rechargeable batteries
- Do not connect the optional power unit when using standard batteries (e.g. alkaline)!

#### **Technical specifications:**

Power consumption:	3,00 W
Frequency range:	100 - 10000 Hz
Dimensions:	Width: 20 cm
	Depth: 8 cm
	Height: 5 cm
Weight:	0,51 kg

#### Logistic

EAN / GTIN: 4026397231632 Weight: 0,63 kg Length: 0.27 m Width: 0.14 m Heigth: 0.07 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Waistband amplifier + active speaker:	
Power supply:	9 V DC
via power unit:	9 V DC, 300 mA
via batteries:	6 x 1.5 V Mignon (AA)
Nominal power output:	3 W RMS
Maximum power output:	5 W
Distortion:	5 %
S/N-ratio:	50 dB
Operating time:	
Mains operation:	unlimited
Battery operation:	6-8 hours
Recharging time:	7-10 hours
Dimensions:	200 x 80 x 50 mm
Headset microphone:	
Туре:	Uni-directional electret headset microphone
Directivity pattern:	Cardioid directivity pattern
Sensitivity:	-70 dB (±3 dB)
Impedance:	200 ohms
Operation voltage:	1.5 V - 10 V
Current consumption:	approx. 0.5 mA
Cable-length:	approx. 1 m
Connection:	via 3.5 mm jack plug (1/8")
Dimensions:	220 x 140 x 140 mm