

## **OMNITRONIC COMBO-500 Active-PA-System**

Portable 500 W PA system









# The article is no longer in our assortment.

#### Features:

- Ultra-portable all-in-one PA system for mobile live and DJ applications
- Detachable 8-channel power mixer with dynamics processor and digital echo effect
- Dual Class D amplifier (2 x 250 W RMS) with SMPS
- 2 detachable full-range speaker systems, each with 25 cm woofer and 25 mm tweeter, bass reflex system and flange for speaker stands
- 4 mono input channels mic/line with +15 V phantom power
- 2 stereo line input channels
- 2-band EQ and level control per channel
- Channel 1 and 2 with switchable compressor/limiter
- Digital echo effect, variably adjustable
- Precise 6-digit LED level display
- Master section with level control and EQ selector music/speech
- Adjustable monitor output
- Recording output
- Convenient accessory compartment
- Delivery includes 2 speaker cables and power cable

#### **Technical specifications:**

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	600,00 W
Frequency range:	55 - 20000 Hz
Dimensions:	Width: 50 cm

### Logistic

EAN / GTIN: 4026397482959 Weight: 23,75 kg Length: 0.71 m Width: 0.40 m Heigth: 0.58 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Depth: 32 cm
Amplifier power:	Height: 29 cm 2 x 250 W RMS at 4 ohms
Amplifier power:	
Speaker systems:	25 cm speaker (10"), 25 mm tweeter (1")
Sensitivity:	94 dB
Inputs:	
MIC, mono	4 x XLR
LINE, stereo	1 x 6.3 mm jack L/R, 2 x stereo RCA
Outputs:	
Monitor:	6.3 mm jack L/R
Record:	stereo RCA
Speakers:	6.3 mm jack L/R
Dispersion angle:	90° x 60°
Dimensions (L x W x H):	
Speakers:	500 x 320 x 290 mm
Mixer:	320 x 180 x 90 mm
Weight:	22 kg