

OMNITRONIC LI-105W Wall Speaker white

5" full-range speaker, 16 ohms, 50 W RMS



The article is no longer in our assortment.

Features:

- Dedicated 1-way system for fixed installation
- 13 cm full-range speaker (5")
- Attractive MDF cabinet 9/15 mm
- Scratch-resistant lacquer surface in black or white
- Movable mounting bracket for ceiling or wall installation
- Steel grille
- Spring clamps for serial connection
- For indoor PA applications
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles

Technical specifications:

| Power: | Program: 100W Rated: 50W RMS |
|--------------------|--|
| Frequency range: | 150 - 20000 Hz |
| Sensitivity: | 93 dB |
| Max. SPL: | 110 dB |
| Dispersion angle: | 100° x 100° |
| Impedance: | 16 ohms |
| Attachment system: | Panning and tilting mounting bracket for ceiling or wall installation in most varying angles |



EAN / GTIN: 4026397528169 Weight: 3,55 kg Length: 0.19 m Width: 0.18 m Heigth: 0.20 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| Connections: | Speaker via spring terminal | |
|------------------|-----------------------------|--|
| Speaker: | 1 x woofer 5" | |
| Type of speaker: | On ceiling/on wall speaker | |
| Color: | White | |
| Dimensions: | Width: 16 cm | |
| | Depth: 15 cm | |
| | Height: 16 cm | |
| Weight: | 3,30 kg | |