

OMNITRONIC LI-204B MK2 2-Way Top

Speaker with mount, 4" woofer, 1" dome tweeter, 30 W RMS







The article is no longer in our assortment.

Features:

- Dedicated full-range bassreflex system for fixed installation
- 10 cm (4") bass speaker and 25 mm (1") horn tweeter
- Attractive trapezoidal cabinet made of 8/12 mm plywood
- Scratch-resistant lacquer surface in black or white
- Supplied with movable mounting bracket for ceiling or wall installation
- Impact-resistant steel grille with acoustic foam
- 2 x M10 thread inserts
- For PA applications in restaurants, bars, discos and shops
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles

Technical specifications:

Power:	Program: 60W
	Rated: 30W RMS
Frequency range:	100 - 20000 Hz
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles
Speaker:	1 x woofer 4"
Color:	Black
Dimensions:	Width: 15,2 cm
	Depth: 13,6 cm
	Height: 24,5 cm

Logistic

EAN / GTIN: 4026397493917 Weight: 3,25 kg Length: 0.17 m Width: 0.15 m Heigth: 0.27 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

cm calotte (1")
erminal