

OMNITRONIC I-212, 2-way top, 150W

For perfect sound presentation

GTIN: 4026397325980



The article is no longer in our assortment.

Features:

- 2-way speaker-system
- For a wide frequency range
- Wide dynamic range with almost linear frequency range
- Also perfect for decentral sound surroundings
- Bass-reflex system
- With flange for speaker-stand installation etc. (I-210 and I-212)
- Not intended for heavy-duty road use
- Can be used lying, standing, on a subwoofer, on a speaker stand or stand or suspended

Technical specifications:

| Power: | Program: 300W Rated: 150W RMS |
|------------------|--|
| Frequency range: | 65 - 20000 Hz |
| Sensitivity: | 90 dB (1W/1m) |
| Max. SPL: | 111 dB |
| Connections: | Input: speaker via 2 x speaker built-in socket (F) |
| Speaker: | 1 x woofer 12" |
| Dimensions: | Width: 57 cm |
| | Depth: 40 cm |
| | Height: 36,5 cm |









Logistic

EAN / GTIN: 4026397325980 Weight: 12,95 kg Length: 0.40 m Width: 0.38 m Heigth: 0.56 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| Weight: | 11,40 kg |
|-------------------------|--------------------------------------|
| Components: | 30 cm woofer (12"), 2.5 cm horn (1") |
| Connection: | 2 Speaker sockets |
| Sensitivity: | 90 dB |
| Maximum SPL: | 111 dB |
| Dispersion angle: | 80° x 50° |
| Dimensions (H x W x D): | 570 x 400 x 365 mm |