

OMNITRONIC AZX-112A PA Subwoofer active 300W

Active 12" PA bassreflex subwoofer, 300 W RMS

Art. No.: 11039038

GTIN: 4026397638899



Features:

- 30 cm (12") bass speaker with 63 mm voice coil
- Class D amplifier with 300 W
- XLR inputs and parallel outputs L/R
- XLR output L/R with high-pass filter
- Adjustable crossover frequency 80-200 Hz
- Black metal grille with acoustic foam
- Rugged carrying handle
- For application areas such as: Clubs/dancing school; installation; mobile use; mobile djs / entertainer; rental

Logistic

EAN / GTIN: 4026397638899

Weight: 24,20 kg

Length: 0.51 m

Width: 0.57 m

Height: 0.47 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	650 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 3.15 A fuse replaceable
Power:	Rated: 300W RMS
Frequency range:	40 - 250 Hz

Sensitivity:	93 dB (1W/1m)
Attachment system:	M20 thread
Circuitry:	Class D
Control elements:	Phase reversal switch
Controls:	Limiter
Status LED:	Limit, power, signal
Connections:	Input: line via 2 x 3-pin XLR Output: line via 2 x 3-pin XLR Output: high-pass via 2 x 3-pin XLR
Crossover frequency:	80-200 Hz
Speaker:	1 x woofer 12" Voice coil lows 2.5"
Type of speaker:	Subwoofer
Type of construction:	Vented
Carrying handle:	1 pc/pcs
Material:	MDF (medium density fiberboard), 15 mm
Color:	Black, textured coating, painted
Dimensions:	Width: 50 cm Depth: 57.5 cm Height: 45 cm
Weight:	22.70 kg

Scope of delivery:

1 x user manual
1 x bass
1 x power cord