

OMNITRONIC AZX-118A PA Subwoofer active 400W

Active 18" PA bassreflex subwoofer, 400 W

Art. No.: 11039046

GTIN: 4026397638936



List price: 629.51 €

incl. 19% VAT.

Features:

- 46 cm (18") bass speaker with 76 mm voice coil
- Class D amplifier with 400 W
- XLR inputs and parallel outputs L/R
- XLR output L/R with high-pass filter
- Adjustable crossover frequency 80-200 Hz
- Phase reversal switch
- Limiter for overload protection
- Limit, signal and power LED
- M20 metal flange for mounting top speakers
- Housing made of 15 mm MDF
- Scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- 1 rugged carrying handle

Logistic

EAN / GTIN: 4026397638936

Weight: 35,85 kg

Length: 0.68 m

Width: 0.67 m

Height: 0.61 m

Bulky product

Technical specifications:

| | |
|--------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 650 W |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Rated power: | 400 W RMS |
| Frequency range: | 40 - 250 Hz |

| | |
|----------------------|--|
| Sensitivity: | 95 dB (1W/1m) |
| Crossover frequency: | 80-200 Hz |
| Attachment system: | M20 thread |
| Circuitry: | Class D |
| Connections: | Input: line via 2 x 3-pin XLR Output: line via 2 x 3-pin XLR Output: high-pass via 2 x 3-pin XLR |
| Speakers: | 1 x woofer (18") approx. 45 cm Voice coil lows (2.5") approx. 6.35 cm |
| Type of speaker: | Subwoofer |
| Type: | Vented |
| Carrying handle: | 1 pc/pcs |
| Material: | MDF (Medium-density fibreboard), 15 mm |
| Dimensions: | Width: 66,5 cm Depth: 66,5 cm |
| Weight: | 33,65 kg |