

OMNITRONIC MOLLY-12A Subwoofer active black

Active 12" subwoofer with DSP and Bluetooth

Art. No.: 11039050

GTIN: 4026397680119



Features:

- 12" bassreflex subwoofer with DSP and 700 watts RMS power
- Flexibly extendable with MOLLY-6 satellites for 2.1 and 4.1 configurations
- DSP-controlled class D amplifier (500 W + 2 x 100 W)
- Separate volume control for subwoofer and satellites
- Stereo/mono selection
- Digital signal processor
- DSP presets: FLAT; DJ; LIVE; VOICE
- The device is cooled by temperature-controlled fan
- Control via Bluetooth
- Operating range up to 10m
- Black metal grille with acoustic foam
- 2 Rugged carrying handles
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; installation; home entertainment; restaurants, bars and hotels; product presentations and lectures

Logistic

EAN / GTIN: 4026397680119

Weight: 23,85 kg

Length: 0.62 m

Width: 0.52 m

Heigh: 0.47 m

Technical specifications:

|                    |                        |
|--------------------|------------------------|
| Power supply:      | 230 V AC, 50 Hz        |
| Power consumption: | 1000 W                 |
| Protection class:  | Protection class I     |
| Output power:      | 1 x 500 W RMS          |
|                    | 2 x 100 W RMS (8 ohms) |
|                    | 2 x 200 W RMS (4 ohms) |

|                        |                                                                                                                                                                                                                                                                         |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power connection:      | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                                                                                                                                                                        |
| Device fuse:           | 5 x 20 mm, T 5 A fuse replaceable                                                                                                                                                                                                                                       |
| Frequency range:       | 40 - 160 Hz                                                                                                                                                                                                                                                             |
| Sensitivity:           | 103 dB                                                                                                                                                                                                                                                                  |
| Max. SPL:              | 128 dB                                                                                                                                                                                                                                                                  |
| DSP:                   | Digital signal processor                                                                                                                                                                                                                                                |
| DSP presets:           | FLAT; DJ; LIVE; VOICE                                                                                                                                                                                                                                                   |
| Cooling:               | Temperature-controlled fan                                                                                                                                                                                                                                              |
| Control:               | Bluetooth                                                                                                                                                                                                                                                               |
| Bluetooth device name: | Omnitronic                                                                                                                                                                                                                                                              |
| Range:                 | Range up to 10m                                                                                                                                                                                                                                                         |
| Attachment system:     | Flange: M20 thread                                                                                                                                                                                                                                                      |
| Circuitry:             | Class D                                                                                                                                                                                                                                                                 |
| Control elements:      | Phase reversal switch, level control per channel, power switch, connect                                                                                                                                                                                                 |
| Controls:              | Softstart; short-circuit; limiter; Overvoltage; overheat                                                                                                                                                                                                                |
| Status LED:            | Signal, power, limit, fault, DSP presets                                                                                                                                                                                                                                |
| Connections:           | Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)<br>Input: line via 1 x 3.5 mm jack (stereo) mounting version<br>Input: line via 1 x stereo RCA<br>Output: line via 2 x 3-pin XLR<br>Output: top via 2 x speaker built-in socket (F) |
| Input channels:        | 1 x stereo via combination socket or RCA or Bluetooth, channel control via rotary dial                                                                                                                                                                                  |
| Speaker:               | 1 x woofer 12"<br>Basket material: steel<br>Conematerial: cardboard/paper<br>Voice coil lows 3"                                                                                                                                                                         |
| Type of speaker:       | Subwoofer                                                                                                                                                                                                                                                               |
| Type of construction:  | Vented                                                                                                                                                                                                                                                                  |
| Carrying handle:       | 2 pc/pcs                                                                                                                                                                                                                                                                |
| Material:              | Birch multiplex                                                                                                                                                                                                                                                         |
| Color:                 | Black, textured coating, painted                                                                                                                                                                                                                                        |
| Dimensions:            | Width: 47 cm<br>Depth: 57 cm<br>Height: 40 cm                                                                                                                                                                                                                           |
| Weight:                | 22.10 kg                                                                                                                                                                                                                                                                |
| Cable length:          | 3 m                                                                                                                                                                                                                                                                     |

## Scope of delivery:

1 x bass  
 1 x power cord  
 2 x speaker cable  
 1 x user manual  
 1 x declaration of conformity