

## OMNITRONIC ROD-1043 Active Column Speaker System

Mobile column PA system with DSP, mixer, stereo Bluetooth link, 350 W RMS system

Art. No.: 11039102

GTIN: 4026397747164



**List price: 534.31 €**

incl. 19% VAT.

### Features:

- Excellent sound quality and high transmission range
- Stereo Bluetooth link for wireless stereo operation with 2 systems linked together
- Metal grille
- **bass**
- 2 recessed carrying handles
- 4 plastic feet
- **integrated amplifier module**
- Digital signal processor
- DSP presets: FLAT; CLUB; VOICE; BASS BOOST; BASS REDUCTION
- Control via Bluetooth
- Bluetooth: operating range up to 10m in buildings

#### Package contents

- 1 x bass, 1 x top, 1 x distance tube, 1 x power cord, 1 x user manual, 1 x speaker cable, 1 x declaration of conformity

### Logistic

EAN / GTIN: 4026397747164

Weight: 23,00 kg

Length: 0.53 m

Width: 0.38 m

Height: 0.59 m

### Technical specifications:

Output power: 350 W RMS system

Frequency range: 42 - 20000 Hz system

Max. SPL: 125 dB system

Weight: 20,00 kg

Bass

Frequency range:	42 - 150 Hz
Impedance:	1 x 4 ohms bass
Attachment system:	M20 thread
Speaker:	1 x woofer 10" with ferrit magnet Basket material: steel Voice coil lows 2" Conematerial: cardboard/paper
Type of speaker:	Subwoofer
Type of construction:	Vented
Recessed carrying handle:	2 pc/pcs
Transport aid:	4 x plastic feet
Material:	MDF (medium density fiberboard), 16 mm
Color:	Black
Dimensions:	Width: 32 cm Depth: 46,5 cm Height: 44,5 cm
Weight:	16,5 kg
Integrated amplifier module	
Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 250 W
Protection class:	Protection class I
Output power:	1 x 200 W RMS LF 1 x 150 W RMS (4 ohms) HF
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Device fuse:	5 x 20 mm, T 2,5 A fuse serviceable
DSP:	Digital signal processor
DSP presets:	FLAT; CLUB; VOICE; BASS BOOST; BASS REDUCTION
Control:	Bluetooth
Bluetooth:	Version: 5,3 with stereo link (TWS)
Bluetooth device name:	ROD-1043
Range:	Bluetooth: range up to 10m in buildings
Carrier frequency:	2,4 GHz
Circuitry:	Class D
Control elements:	Level control, power switch, Input sensitivity switch
Controls:	Short-circuit; DC voltage; limiter; overload
Status LED:	Signal, limit, DSP presets, pairing, link
Connections:	Input: mic/line via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: line via 1 x stereo RCA Output: line via 1 x 3-pin XLR (M) mounting version Output: top via 1 x speaker built-in socket (F)
Input channels:	1 x stereo via RCA or Bluetooth, channel control via rotary dial

	1 x mono with mic-line switch via Combination socket (XLR/jack), channel control via rotary dial
Crossover frequency:	150 Hz
Top	
Power:	Program: 160W Rated: 80W AES
Frequency range:	150 - 20000 Hz
Sensitivity:	90 dB (1W/1m)
Dispersion angle:	100° x 20°
Impedance:	1 x 4 ohms top
Attachment system:	Flange: Ø 25mm
Connections:	Input: top via 1 x speaker built-in socket (F)
Speaker:	4 x full range loudspeaker 3" with neodymium magnet  Basket material: steel Voice coil full range loudspeaker 0,75" Conematerial: cardboard/paper
Type of speaker:	Column speaker
Type of construction:	Closed Box
Material:	Plastic hard
Dimensions:	Width: 8,5 cm Depth: 10,5 cm Height: 45 cm
Weight:	1,43 kg
Distance tube	
Attachment system:	M20 thread Pivot: Ø 25mm
Dimensions:	Height: 103 cm Diameter: Ø 3 cm
Weight:	0,74 kg
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	1,80 m
Speaker cable	
Cable construction:	1 x speaker cable
Cable length:	2 m