

OMNITRONIC PAS-212+ 2-Way Top

PA speaker with 12" woofer, 1.4" horn, 300 W RMS, 8 ohms











The article is no longer in our assortment.

Features:

- PA speaker system for medium-sized and large discotheques
- Rugged full-range top speaker qualified for suspended installation
- Rotatable constant directivity horn (asymmetrical) with coil-driver
- Passive 2-way crossover, PTC tweeter protection
- Bass-reflex system for powerful, dry bass
- Balanced frequency range with high sound-pressure
- Very high durability
- Optimized for combination with PAS subwoofers
- Scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Flange for stand installation
- Trapezoidal wooden housing with monitor shape
- Can be used lying, standing, on a subwoofer, on a stand or suspended
- Suitable for car transport
- The combination of several PAS speakers allows for large PA systems
- With rigging points

Technical specifications:

Power:	Program: 600W
	Rated: 300W RMS
Frequency range:	60 - 20000 Hz
Sensitivity:	97 dB

Logistic

EAN / GTIN: 4026397552003 Weight: 19,40 kg Length: 0.44 m Width: 0.41 m Heigth: 0.67 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Max. SPL:	124,5 dB
Dispersion angle:	50° to 100° x 55°
Impedance:	8 ohms
Flying points:	12 x M10 thread
Connections:	Input: speaker via 2 x speaker built-in socket (F)
Crossover frequency:	2200 Hz
Speaker:	1 x woofer 12"
	1 x horn 1,35"
Type of speaker:	Compact cabinet speaker
Dimensions:	Width: 36,1 cm
	Depth: 33,4 cm
	Height: 58,4 cm
Weight:	17,65 kg