

# **OMNITRONIC PAS-210PRO 2-way top**

2-way speaker system for PA applications

Art. No.: 11039442 GTIN: 4026397438383



# The article is no longer in our assortment.

## Features:

- PA speaker system for medium-sized and large discotheques
- Rugged full-range top speaker qualified for suspended installation
- Rotatable constant directivity horn (asymmetrical) with coil-driver
- Passive 2-way crossover, PTC tweeter protection
- Bass-reflex system for powerful, dry bass
- Balanced frequency range with high sound-pressure
- Very high durability
- Optimized for combination with PAS subwoofers
- Scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Flange for stand installation
- Trapezoidal wooden housing with monitor shape
- Can be used lying, standing, on a subwoofer, on a speaker stand or stand or suspended
- Suitable for car transport
- The combination of several PAS speakers allows for large PA systems

#### **Technical specifications:**

| Frequency range: | 65 - 20000 Hz |
|------------------|---------------|
| Dimensions:      | Width: 28 cm  |
|                  | Depth: 32 cm  |
|                  | Height: 54 cm |
| Weight:          | 14,70 kg      |

### Logistic

EAN / GTIN: 4026397438383

Weight: 16,50 kg Length: 0.41 m Width: 0.37 m Heigth: 0.65 m

| Rated power:            | 250 W RMS                            |
|-------------------------|--------------------------------------|
| Program power:          | 500 W                                |
| Components:             | 25 cm woofer (10"), 2.5 cm horn (1") |
| Connection:             | 2 Speaker sockets                    |
| Sensitivity:            | 96 dB                                |
| Maximum SPL:            | 120 dB                               |
| Impedance:              | 8 ohms                               |
| Crossover frequency:    | 2 kHz                                |
| Dispersion angle:       | 50-100° x 55°                        |
| Dimensions (H x W x D): | 540 x 280 x 320 mm                   |